



INDUSTRIAL PNEUMATIC

SOLIDEAL ED PLUS



camsso.co

solideal
becoming CAMSO



Untitled-1

Every day, we ask ourselves: "Is there a better way?"

At Camso, we understand that customers' needs vary and require the right tires to lift and move material in numerous applications. Like you, we believe in speed, continuous motion and constant flow. Uptime is the only time. As a true partner, our extensive distribution and service network gives you access to our products and services, and our market knowledge, R&D centres and great familiarity with the users of our products and services nurture our vision of bringing the lowest operating cost solution to the off-the-road mobility market.

solideal
becoming CAMSO



SOLIDEAL ED PLUS

TIRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE (1)		ACTUAL TIRE DIMENSIONS				INFLATION PRESSURE (psi)	LOAD INDEX & SPEED SYMBOL	LOAD CAPACITY (2) Counterbalanced lift trucks				
				Recom- mended	Alternative	Overall diameter (inch)	Section width (inch)	Original Tread Depth	Static Loaded Radius			Up to 16 mph		Up to 20 mph		
												Load wheel	Steering wheel	Load wheel	Steering wheel	
				5.00-8 (5.70-8)	8	JS2	août-90	3.00D	3.25I/3.75I			18.4	5.2	0.5	8.3	119.7
5.00-8 (5.70-8)	10	JS2	août-90	3.00D	3.25I/3.75I	18.3	5.2	0.5	8.2	145.0	111	A5	3120	2403	3009	2238
16X6-8 (4.80-8)	14	V3-02-05	130-8	4.33R	-	16.5	5.8	0.5	7.5	123.3	111	A5	3120	2403	3009	2238
18X7-8 (180/70-8)	14	V3-02-05	130-8	4.33R	5.00F	17.8	6.2	0.6	16.8	130.5	121	A5	4156	3197	4001	2976
18X7-8 (180/70-8)	16	V3-02-05	130-8	4.33R	5.00F	18.1	6.2	0.6	8.1	145.0	125	A5	4729	3638	4552	3384
6.00-9	10	JS2	125-9	4.00E	-	20.7	5.9	0.5	9.3	123.3	118	A5	3781	2910	3638	2712
6.00-9	12	JS2	125-9	4.00E	-	21.1	6.4	0.5	9.5	145.0	121	A5	4156	3197	4001	2976
21X8-9 (200/75-9)	14	JS2	180-9	6.00E	7.00E	20.9	8.0	0.8	9.4	130.5	131	A5	5589	4299	5379	4001
21X8-9 (200/75-9)	16	JS2	180-9	6.00E	7.00E	21.1	8.0	0.8	9.5	145.0	134	A5	6074	4674	5842	4343
6.50-10	10	JS2	140-10	5.00F	5.50F	23.1	6.7	0.6	10.4	112.4	122	A5	4299	3307	4134	3075
6.50-10	12	JS2	140-10	5.00F	5.50F	23.1	7.3	0.6	10.4	130.5	125	A5	4729	3638	4552	3384
6.50-10	14	JS2	140-10	5.00F	5.50F	23.2	7.3	0.6	10.5	145.0	128	A5	5159	3968	4960	3693
23X9-10 (225/75-10)	16	JS2	180-10	6.50F	-	23.0	9.0	0.8	10.2	116.0	137	A5	6592	5070.58	6338	4718
23X9-10 (225/75-10)	18	JS2	180-10	6.50F	-	22.8	9.1	0.8	10.3	130.5	139	A5	6967	5357.178	6702	4982
23X10-12 (250/55-12)	16	JS2	210-12	8.00G	-	23.3	9.4	0.6	10.6	141.4	143	A5	7793	6008	7507	5589
27X10-12 (250/75-12)	16	V3-02-05	210-12	8.00G	-	26.9	9.9	0.7	12.1	116.0	146	A5	8598	6614	8267	6151
27X10-12 (250/75-12)	20	V3-02-05	210-12	8.00G	-	26.9	9.9	0.7	12.1	130.5	152	A5	10174	7826	9788	7275
7.00-12	12	TR75A	135-12	5.00S	-	26.6	7.6	0.6	12.0	123.3	133	A5	5908	4541	5677	4222
7.00-12	14	TR75A	135-12	5.00S	-	26.7	7.2	0.6	12.0	130.5	134	A5	6074	4674	5842	4343
28X9-15 (8.15-15 & 225/75-15)	12	V3-02-08	180-15 HD	7.00	-	28.3	8.8	0.8	13.0	119.7	142	A5	7595	5842	7308	5434
28X9-15 (8.15-15 & 225/75-15)	14	V3-02-08	180-15 HD	7.00	-	28.1	8.8	0.8	12.6	130.5	145	A5	8311	6393	7992	5941
28X9-15 (8.15-15 & 225/75-15)	16	V3-02-08	180-15 HD	7.00	-	28.1	8.8	0.8	12.9	141.4	148	A5	9028	6944	8686	6459
250-15	16	TR77A	180-15 HD	7.50	7.00	28.8	9.2	0.8	13.2	119.7	150	A5	9601	7385	9237	6867
250-15	18	TR77A	180-15 HD	7.50	7.00	28.9	9.1	0.8	13.2	137.8	153	A5	10461	8047	10064	7485
300-15	18	TR78A	180-15 HD	8.00	-	32.5	11.5	1.0	14.7	116.0	161	A5	13261	10196	12743	9480
7.00-15	12	TR75A	180-15	5.50	5.00	29.7	7.3	0.7	13.5	119.7	138	A5	6768	5203	6504	4839
7.00-15	14	TR75A	180-15	5.50	5.00	30.0	8.0	0.7	13.5	130.5	141	A5	7385	5677	7099	5280
7.50-15	14	TR75A	180-15	6.00	5.50/6.50	30.9	8.3	0.8	14.1	134.2	144	A5	8025	6173	7716	5743
8.25-15 (7.50-15(32))	14	TR77A	180-15	6.50	6.00/7.00	33.2	9.1	0.7	15.0	116.0	149	A5	9314	7165	8962	6669
8.25-15 (7.50-15(32))	16	TR77A	180-15	6.50	6.00/7.00	33.3	9.9	0.7	15.0	134.2	152	A5	10174	7826	9788	7275

TIRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE (1)		ACTUAL TIRE DIMENSIONS				INFLATION PRESSURE (psi)	LOAD INDEX & SPEED SYMBOL	LOAD CAPACITY (2) Counterbalanced lift trucks				
				Recom- mended	Alternative	Overall diameter (inch)	Section width (inch)	Original Tread Depth	Static Loaded Radius			Up to 16 mph		Up to 20 mph		
												Load wheel	Steering wheel	Load wheel	Steering wheel	
				9.00-20	14	V3-02-14	200-20	7.00	6.50/7.50			41.2	11.3	0.9	18.7	130.5
10.00-20	16	V3-02-14	200-20	7.50	7.00/8.00	41.7	11.2	0.8	18.9	130.5	164	A5	14330	11023	13779	10251
12.00-20	18	V3-02-14	200-20	8.50	8.00/9.00	44.6	13.0	1.3	20.2	130.5	172	A5	18056	13889	17361	12919
12.00-20	20	V3-02-14	200-20	8.50	8.00/9.00	44.6	13.0	1.3	20.2	145.0	175	A5	19775	15212	19015	14143



UNIQUE STAGGERED TREAD DESIGN

- Reduces vibration which increase life and operator comfort



WIDE FLAT PROFILE AND DEEP TREAD

- Improves traction and life



WIDE SIDEWALL

- Provides high side impact resistance
Two times more rubber than (standard) tires



Remarks

- (1) Consult tire and wheel manufacturer for confirmation of the suitability of the tire/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tire are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tire size

** Table shows standard valves. Other valves on request.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

AUTHORIZED DISTRIBUTOR: