



# OTANI®

AGRICULTURAL TIRE CATALOG 2018



05/2018





T-22

T-25

F-30

F-32

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	MAXIMUM SPEED	STANDARD RIM WIDTH	INFLATION PRESSURE		MAXIMUM LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
						km/h	inch	psi	kgf/cm <sup>2</sup>	kg	mm	mm	mm
14"	<b>NEW</b> 6-14	4	F-33	R1/G1	TT	30	5.00	28	1.97	305	162	655	28
	<b>NEW</b> 7-14	4	F-33	R1/G1	TT	30	5.00	26	1.83	370	178	687	28
	6.50-14	6	F-33	R1	TT	30	4.50	46	3.23	715	183	699	19
15"	4.00-15	6	T-22	I1	TT	30	3.00	64	4.50	420	114	610	10
16"	6.00-16	6	T-22	I1	TT	30	4.00	52	3.66	515	177	740	15
		8	T-22	I1	TT	30	4.00	68	4.78	615	180	750	15
	7-16	4	F-33	R1/G1	TT	30	6.00	26	1.83	405	183	740	26
	7.50-16	8	F-30	-	TT	30	6.00	40	2.81	775	207	893	57
		4	F-33	R1	TT	30	5.50	35	2.46	748	216	814	20
		8	F-33	R1	TT	30	5.50	56	3.94	870	220	816	20
		8	F-34	R1	TT	30	5.50	56	3.94	875	208	814	25
		6	T-22	I1	TT	30	5.50	44	3.09	670	210	814	20
		8	T-22	I1	TT	30	5.50	56	3.94	776	210	814	20
	8	T-25	I1	TT	30	5.50	56	3.94	776	208	805	17	
	8-16	4	F-33	R1/G1	TT	40	6.00	23	1.62	475	211	790	31
	9-16	6	F-33	R1/G1	TT	30	5.50	32	2.25	748	245	850	30
	9.00-16	8	F-33	R1	TT	30	5.50	59	4.15	875	234	843	20
		10	T-22	I1	TT	30	7.00	52	3.66	1500	232	848	17
10.00-16	8	T-22	I1	TL	30	8.00	44	3.09	1060	272	898	19	
11.00-16	8	T-22	I1	TL	30	10.00	40	2.81	1180	305	947	22	
18"	7.50-18	8	F-33	R1	TT	30	5.50	59	4.15	875	210	860	20
		8	T-22	I1	TT	30	5.50	55	3.87	875	220	864	20
	8-18	4	F-33	R1/G1	TT	40	7.00	23	1.62	520	221	840	31
		6	F-33	R1/G1	TT	40	7.00	34	2.40	650	222	840	31
		6	F-35	R1/G1	TT	40	7.00	34	2.40	650	222	845	34
		8	F-35	R1/G1	TT	40	7.00	42	2.95	850	222	845	34
20"	8.3-20	6	F-35	R1	TT	40	W7	34	2.40	710	208	890	30
	11.2-20	8	F-35	R1	TT	40	W9	36	2.53	1150	280	1010	30
22"	9.5-22	6	F-36	R1	TT	40	W8	31	2.18	900	240	1010	40
24"	8.3-24	6	F-35	R1	TT	40	W7	34	2.40	810	208	996	30
		6	F-35	R1	TT	40	W8	32	2.25	940	241	1048	30
	9.5-24	6	F-37	R1	TT	40	W8	32	2.25	940	241	1085	57
		4	F-37	R1	TT	40	W10	17	1.20	900	282	1098	57
	11.2-24	6	F-37	R1	TT	40	W10	26	1.83	1115	284	1103	57
		8	F-39	R1	TT	30	W10	34	2.40	1235	284	1110	42
	12.4-24	4	F-37	R1	TT	40	W11	17	1.20	945	318	1160	57
		6	F-37	R1	TT	40	W11	24	1.69	1200	320	1165	57
		8	F-37	R1	TT	40	W11	32	2.25	1415	322	1170	57




**F-33**
**F-34**
**F-35**
**F-36**

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	MAXIMUM SPEED	STANDARD RIM WIDTH	INFLATION PRESSURE		MAXIMUM LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
						km/h	inch	psi	kgf/cm <sup>2</sup>	kg	mm	mm	mm
24"	12.4/11-24	8	F-33	R1	TT	40	W11	32	2.25	1415	286	1160	28
		10	F-33	R1	TT	40	W11	36	2.53	1530	288	1160	28
		12	F-33	R1	TT	40	W11	44	3.09	1630	288	1161	28
	13.6-24	6	F-37	R1	TT	40	W12	23	1.61	1340	345	1210	57
		8	F-37	R1	TT	40	W12	32	2.25	1615	348	1215	57
		8	F-39	R1	TT	30	W12	32	2.25	1615	346	1212	42
	14.9-24	12	F-39	R1	TT	30	W12	36	2.53	1660	348	1215	42
		8	F-32	R1	TT/TL	40	W13	26	1.83	1600	389	1240	30
		12	F-32	R1	TT/TL	40	W13	38	2.67	2000	395	1245	30
		6	F-33	R1	TT/TL	30	W13	20	1.41	1510	378	1280	35
		8	F-33	R1	TT	30	W13	26	1.83	1600	385	1285	35
		12	F-33	R1	TT/TL	30	W13	38	2.67	2000	386	1286	35
		8	F-37	R1	TT	40	W13	26	1.83	1600	378	1285	60
		8	G-45	R4	TT/TL	40	W13	30	2.10	2300	397	1271	27
		10	G-45	R4	TT/TL	40	W13	36	2.53	2800	405	1272	27
	16.9-24	8	G-45	R4	TT/TL	40	W15	28	1.97	2650	440	1360	27
		10	G-45	R4	TT/TL	40	W15	32	2.25	2900	445	1362	27
		12	G-45	R4	TT/TL	40	W15	38	2.67	3250	450	1363	27
	17.5L-24	8	G-45	R4	TT/TL	40	W15	26	1.83	2430	450	1300	27
		10	G-45	R4	TT/TL	40	W15	32	2.25	2800	456	1310	27
		12	G-45	R4	TT/TL	40	W15	36	2.53	2995	460	1321	27
18.4-24	10	G-45	R4	TT/TL	40	W16	28	1.97	3350	472	1412	28	
	12	G-45	R4	TT/TL	40	W16	36	2.53	3750	480	1414	28	
19.5L-24	10	G-45	R4	TT/TL	40	W16	30	2.10	3000	495	1312	27	
	12	G-45	R4	TT/TL	40	W16	34	2.39	3450	496	1314	27	
	12	G-45	R4	TT/TL	40	W16	40	2.80	3750	498	1315	27	
21L-24	12	G-45	R4	TT/TL	40	W18	34	2.39	3447	558	1410	28	
26"	13.6-26	4	F-37	R1	TT	40	W12	14	1.00	1065	343	1285	57
		6	F-37	R1	TT	40	W12	23	1.62	1400	345	1260	57
		8	F-37	R1	TT	40	W12	26	1.83	1600	345	1261	57
	23.1-26	6	F-35	R1	TT	40	W12	23	1.62	1400	345	1276	47
		8	F-35	R1	TT	40	W12	26	1.83	1600	348	1280	47
		8	F-38	R1	TT/TL	40	W20	16	1.13	2575	600	1595	42
		12	F-38	R1	TT/TL	40	W20	20	1.41	3250	610	1600	42
16	F-38	R1	TT/TL	40	W20	32	2.25	3655	615	1605	42		
28"	12.4-28	4	F-37	R1	TT	40	W11	17	1.20	1005	315	1260	53
		6	F-37	R1	TT	40	W11	22	1.55	1275	315	1260	53
	12.4/11-28	8	F-33	R1	TT	30	W11	26	1.83	1500	305	1257	28





F-37

F-38

F-39

F-85

G-45

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	MAXIMUM SPEED	STANDARD RIM WIDTH	INFLATION PRESSURE		MAXIMUM LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
						km/h	inch	psi	kgf/cm <sup>2</sup>	kg	mm	mm	mm
28"	12.4/11-28	10	F-33	R 1	TT	30	W11	32	2.25	1630	306	1259	28
		12	F-33	R 1	TT	30	W11	34	2.39	1730	307	1260	28
	13.6-28	6	F-37	R 1	TT	40	W12	23	1.62	1450	345	1310	57
		8	F-37	R 1	TT	40	W12	28	1.97	1650	348	1313	57
	14.9-28	6	F-35	R 1	TT	40	W13	20	1.41	1610	378	1365	40
		8	F-35	R 1	TT	40	W13	20	1.41	1610	378	1365	40
	16.9-28	8	F-33	R 1	TT	30	W15	28	1.97	1950	430	1430	40
			F-33	R 1	TT	30	W15	28	1.97	2120	435	1435	40
		8	G-45	R 4	TT/TL	40	W15	28	1.97	2800	429	1400	27
		10	G-45	R 4	TT/TL	40	W15	32	2.25	3075	430	1405	27
12		G-45	R 4	TT/TL	40	W15	38	2.67	3450	432	1410	27	
30"	16.9/14-30	8	F-33	R 1	TT	30	W15	24	1.69	2245	438	1483	46
		10	F-33	R 1	TT	30	W15	28	1.97	2455	439	1486	46
		12	F-33	R 1	TT	30	W15	32	2.25	2725	460	1640	46
		14	F-33	R 1	TT	30	W15	38	2.67	3000	463	1644	46
	18.4/15-30	10	F-39	R 1	TT	30	W15	28	1.97	2455	439	1486	53
		8	F-33	R 1	TT	30	16.00	20	1.41	2418	480	1545	46
		10	F-33	R 1	TT	30	16.00	26	1.83	2815	480	1545	46
		12	F-33	R 1	TT	30	16.00	32	2.25	3180	480	1548	46
		8	F-39	R 1	TT	30	W16	20	1.41	2418	480	1544	53
		10	F-39	R 1	TT	30	W16	26	1.83	2815	483	1546	53
32"	12.4-32	6	F-35	R 1	TT	40	W12	23	1.62	1355	315	1265	40
		10	F-39	R 1	TT	30	W15	28	1.97	2418	475	1644	53
34"	16.9/14-34	8	F-39	R 1	TT	30	W15	20	1.41	2360	463	1640	53
		10	F-39	R 1	TT	30	W15	28	1.97	2418	475	1644	53
	18.4-34	6	F-85	R 2	TT	30	W16	16	1.13	2000	491	1722	81
		8	F-33	R 1	TT	30	W16	20	1.41	2565	480	1603	46
38"	13.6-38	8	F-38	R 1	TT	30	W12	32	2.25	1965	345	1555	40
		8	F-38	R 1	TT	30	W14	26	1.83	1850	401	1555	34
	15.5-38	10	F-38	R 1	TT	30	W14	32	2.25	2150	403	1560	34
		8	F-38	R 1	TT	30	W15L	24	1.69	2520	430	1685	40
	16.9-38	10	F-38	R 1	TT	30	W15L	28	1.97	2500	433	1690	40
		6	F-85	R 2	TT	30	W16	16	1.13	2120	483	1795	81
	18.4-38	8	F-85	R 2	TT	30	W16	20	1.41	2430	485	1798	81
		8	F 85	R 2	TT	30	W18	18	1.27	2800	535	1904	85